


# JS12 | Côtes de Sertissage

Crimping diameters

MAJ  
11/04/19



Côtes de sertissages téléchargeables sur : [www.bjflex.com](http://www.bjflex.com)

TOLERANCE SERTISSAGE : 0 / - 0.3

# BEZEK

Diamètre Tuyau	JUPES Ø X long	Paramètres Sertissage	TUYAU / HOSES	
			R1AT	R2T
DN06 1/4 MOD4	JS1206 Ø 23x27	Lg Dénudage	Sans	20
		Ø serti	<b>17.0</b>	<b>17.0</b>
DN08 5/16 MOD5	JS1208 Ø 24x27	Lg Dénudage	Sans	20
		Ø serti	<b>18.7</b>	<b>18.5</b>
DN10 3/8 MOD6	JS1210 Ø 26x32	Lg Dénudage	Sans	24
		Ø serti	<b>21.4</b>	<b>21.3</b>
DN13 1/2 MOD8	JS1213 Ø 30x33.5	Lg Dénudage	Sans	26
		Ø serti	<b>24.8</b>	<b>24.3</b>
DN16 5/8 MOD10	JS1216 Ø 34x37.3	Lg Dénudage	Sans	28
		Ø serti	<b>28.0</b>	<b>28.3</b>
DN19 3/4 MOD12	JS1219 Ø 38x43.5	Lg Dénudage	Sans	30
		Ø serti	<b>32.2</b>	<b>31.9</b>
DN25 1" MOD16	JS1225 Ø 48x47.5	Lg Dénudage	Sans	32
		Ø serti	<b>39.5</b>	<b>39.6</b>
DN32 1"1/4 MOD20	JS1232 Ø 55x51.5	Lg Dénudage		38
		Ø serti		<b>48.5</b>

Attention : les valeurs sont données à titre indicatif, contrôle à la pige de la déformation du nipple

[www.bjflex.com](http://www.bjflex.com)