



JSIK/JSIK13 | Côtes de Sertissage

Crimping diameters

MAJ
05/01/21



Côtes de sertissages téléchargeables sur : www.bjflex.com

TOLERANCE SERTISSAGE : 0 / - 0.3

Diamètre Tuyau	JUPES Ø X long	Paramètres Sertissage	TUYAU / HOSES							
			JSIK					JSIK13		
			R9R	4SH	R12	R15	ULTRA		R13	R15
DN19 3/4	JSIK19 Ø 38X60	Dénudage Ext	52.0	52.0	52.0		52.0			
		Dénudage Int	15.0	15.0	15.0		15.0			
		Ø serti	33.5	33.5	34.1		33.7			
DN25 1"	JSIK25 Ø 46X74.5	Dénudage Ext	65.0	65.0	65.0	65.0	65.0			
		Dénudage Int	17.0	17.0	17.0	17.0	17.0			
		Ø serti	41.0	41.4	41.5	41.7	42			
DN32 1"1/4	JSIK32 Ø 55X88	Dénudage Ext	74.0	74.0	74.0				74.0	74.0
		Dénudage Int	21.5	21.5	21.5			JS IK 13 32	21.5	21.5
		Ø serti	53.0	50.1	49.5				53.8	53.8
DN38 1"1/2	JSIK38 Ø 62X94	Dénudage Ext		81.0	81.0				81.0	81.0
		Dénudage Int		22.0	22.0			JS IK 13 38	22.0	22.0
		Ø serti		57.0	57.2				60.5	60.5
DN50 2"	JSIK50 Ø 78X99	Dénudage Ext		85.0	85.0				85.0	85.0
		Dénudage Int		29.0	29.0			JS IK 13 50	29.0	29.0
		Ø serti		72.0	72.0				77.9	79.0

Attention : les valeurs sont données à titre indicatif, contrôle à la pige de la déformation du nipples

www.bjflex.com